

Déclaration de Performances

Nr. NLD0001-0006-03 (FR)

1. Code d'identification unique:

| | | |
|------------------|------------------------|--------------------------------|
| CLADIROL 36 | MW-EN-13162-T2-WS-MU1 | ² (voir le point 7) |
| CLADIROLL | MW-EN-13162-T2-WS-AFr5 | ¹ (voir le point 7) |
| CLADISOL | MW-EN-13162-T3-WS-AFr5 | ¹ (voir le point 7) |
| CLADISOL E1 | MW-EN-13162-T3-WS-AFr5 | ¹ (voir le point 7) |
| CLADISOL ZS-4 | MW-EN-13162-T3-WS-AFr5 | ¹ (voir le point 7) |
| CLADISOL ZS-6 | MW-EN-13162-T3-WS-AFr5 | ¹ (voir le point 7) |
| FLEX V218 | MW-EN-13162-T2 | ¹ (voir le point 7) |
| FLEX NO18 | MW-EN-13162-T2 | |
| SONEPANEL 36 | MW-EN-13162-T3 | |
| ISOLATIEPLAAT 36 | MW-EN-13162-T3 | |
| COMFI PANEL | MW-EN-13162-T3 | |

2. Elément permettant l'identification du produit de construction:

Nom et Code unique du produit (comme indiqué au point 1).
(Voir étiquette produit pour la traçabilité)

3. Usage prévu (conformément à la spécification technique harmonisée):

Isolation thermique du bâtiment (ThiB)

4. Nom, raison sociale et adresse de contact du fabricant:

SAINT-GOBAIN ISOVER
Parallelweg 20, 4878 AH, Etten-Leur, Nederland

5. Nom et adresse de contact du mandataire:

Non applicable

6. Systèmes d'évaluation et de vérification de la constance des performances:

AVCP Système 1 pour la réaction au feu (Euroclass A1, A2, B, C) & AVCP Système 3 pour les autres caractéristiques
AVCP Système 4 pour la réaction au feu (Euroclass F) & AVCP Système 3 pour les autres caractéristiques

7. Cas des produits couverts par une norme harmonisée:

KIWA (Organisme Notifié n° 0620), a réalisé la détermination du produit type sur la base d'essais type (y compris l'échantillonnage); une inspection initiale de l'établissement de fabrication et un contrôle de la production en usine; une surveillance, une évaluation et une appréciation permanente du contrôle de la production en usine; selon le système 1

Le BDA (Organisme Notifié n°1640) & KIWA (Organisme Notifié n° 0620), ont réalisé la détermination du produit type sur la base d'essais de type, selon le système 3

8. Cas des produits pour lesquels une évaluation technique européenne a été délivrée :
Non applicable

9. Performances déclarées:



Saint-Gobain Isover

Hoofdkantoor • Parallelweg 20, 4878 AH Etten-Leur • Tel: 076 508 00 00 • Handelsregister Breda 20022420 • BTW-nr: NL 009960120B01
Handelsnaam van Saint-Gobain Construction Products Nederland B.V.

Verkoopkantoor Nederland • Stuartweg 1b, 4131 NH Vianen

Les caractéristiques listées ci-dessous se réfèrent à la norme harmonisée EN 13162:2012+A1:2015

| Essential characteristics Requirement clauses in the european standard | CLADIROL 36 | CLADIROLL |
|--|-------------------------|-------------------------|
| Thermal resistance and thermal conductivity (4.2.1) | | 0,036 mW/m.K |
| Thickness (4.2.3) | T2 | T2 |
| Reaction to Fire (4.2.6) | A2-s1,do | A1 |
| Water absorption (4.3.7.1) | < 1 kg / m ² | < 1 kg / m ² |
| Water absorption (4.3.7.2) | NPD | NPD |
| Water vapour transmission (4.3.8) | ≤1 | NPD |
| Release of dangerous substances (4.3.13) | NPD | NPD |
| Sound absorption (4.3.11) | NPD | NPD |
| Dynamic stiffness (4.3.9) | NPD | NPD |
| Thickness (4.3.10.2) | NPD | NPD |
| Compressability (4.3.10.4) | NPD | NPD |
| Air Flow resistivity (4.3.12) | NPD | 5 kPa.s/m ² |
| Air Flow resistivity (4.3.12) | NPD | 5 kPa.s/m ² |
| Continuous glowing combustion (4.3.15) | NPD | NPD |
| Compressive stress or compressive strength (4.3.3) | NPD | NPD |
| Point load (4.3.5) | NPD | NPD |
| Durability characteristics (4.2.7) ^{a,b} | NPD | NPD |
| Thermal resistance and thermal conductivity (4.2.1) ^c | NPD | NPD |
| Durability characteristics (4.2.7) ^d | NPD | NPD |
| Tensile strength perpendicular to faces ^e (4.3.4) | NPD | NPD |
| Compressive creep (4.3.6) | NPD | NPD |
| CE Designation code | MW-EN13162-T2-WS-MU1 | MW-EN13162-T2-WS-AFr5 |
| CE certificatenumber | 0034 | 41531 |

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation



Saint-Gobain Isover

Hoofdkantoor • Parallelweg 20, 4878 AH Etten-Leur • Tel: 076 508 00 00 • Handelsregister Breda 20022420 • BTW-nr: NL 009960120B01
Handelsnaam van Saint-Gobain Construction Products Nederland B.V.

Verkoopkantoor Nederland • Stuartweg 1b, 4131 NH Vianen

| Essential characteristics Requirement clauses in the european standard | CLADISOL | CLADISOL E1 |
|--|-------------------------|-------------------------|
| Thermal resistance and thermal conductivity (4.2.1) | | 0,036 mW/m.K |
| Thickness (4.2.3) | T3 | T3 |
| Reaction to Fire (4.2.6) | A1 | A1 |
| Water absorption (4.3.7.1) | < 1 kg / m ² | < 1 kg / m ² |
| Water absorption (4.3.7.2) | NPD | NPD |
| Water vapour transmission (4.3.8) | NPD | NPD |
| Release of dangerous substances (4.3.13) | NPD | NPD |
| Sound absorption (4.3.11) | NPD | NPD |
| Dynamic stiffness (4.3.9) | NPD | NPD |
| Thickness (4.3.10.2) | NPD | NPD |
| Compressability (4.3.10.4) | NPD | NPD |
| Air Flow resistivity (4.3.12) | 5 kPa.s/m ² | 5 kPa.s/m ² |
| Air Flow resistivity (4.3.12) | 5 kPa.s/m ² | 5 kPa.s/m ² |
| Continuous glowing combustion (4.3.15) | NPD | NPD |
| Compressive stress or compressive strength (4.3.3) | NPD | NPD |
| Point load (4.3.5) | NPD | NPD |
| Durability characteristics (4.2.7) ^{a,b} | NPD | NPD |
| Thermal resistance and thermal conductivity (4.2.1) ^c | NPD | NPD |
| Durability characteristics (4.2.7) ^d | NPD | NPD |
| Tensile strength perpendicular to faces ^e (4.3.4) | NPD | NPD |
| Compressive creep (4.3.6) | NPD | NPD |
| CE Designation code | MW-EN13162-T3-WS-AFr5 | MW-EN13162-T3-WS-AFr5 |
| CE certificate number | 41531 | 41531 |

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation



Saint-Gobain Isover

Hoofdkantoor • Parallelweg 20, 4878 AH Etten-Leur • Tel: 076 508 00 00 • Handelsregister Breda 20022420 • BTW-nr: NL 009960120B01
Handelsnaam van Saint-Gobain Construction Products Nederland B.V.

Verkoopkantoor Nederland • Stuartweg 1b, 4131 NH Vianen

| Essential characteristics Requirement clauses in the european standard | CLADISOL ZS-4 | CLADISOL ZS-6 |
|--|-------------------------|-------------------------|
| Thermal resistance and thermal conductivity (4.2.1) | | 0,036 mW/m.K |
| Thickness (4.2.3) | T3 | T3 |
| Reaction to Fire (4.2.6) | A1 | A1 |
| Water absorption (4.3.7.1) | < 1 kg / m ² | < 1 kg / m ² |
| Water absorption (4.3.7.2) | NPD | NPD |
| Water vapour transmission (4.3.8) | NPD | NPD |
| Release of dangerous substances (4.3.13) | NPD | NPD |
| Sound absorption (4.3.11) | NPD | NPD |
| Dynamic stiffness (4.3.9) | NPD | NPD |
| Thickness (4.3.10.2) | NPD | NPD |
| Compressability (4.3.10.4) | NPD | NPD |
| Air Flow resistivity (4.3.12) | 5 kPa.s/m ² | 5 kPa.s/m ² |
| Air Flow resistivity (4.3.12) | 5 kPa.s/m ² | 5 kPa.s/m ² |
| Continuous glowing combustion (4.3.15) | NPD | NPD |
| Compressive stress or compressive strength (4.3.3) | NPD | NPD |
| Point load (4.3.5) | NPD | NPD |
| Durability characteristics (4.2.7) ^{a,b} | NPD | NPD |
| Thermal resistance and thermal conductivity (4.2.1) ^c | NPD | NPD |
| Durability characteristics (4.2.7) ^d | NPD | NPD |
| Tensile strength perpendicular to faces ^e (4.3.4) | NPD | NPD |
| Compressive creep (4.3.6) | NPD | NPD |
| CE Designation code | MW-EN13162-T3-WS-AFr5 | MW-EN13162-T3-WS-AFr5 |
| CE certificate number | 41531 | 41531 |

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation



Saint-Gobain Isover

Hoofdkantoor • Parallelweg 20, 4878 AH Etten-Leur • Tel: 076 508 00 00 • Handelsregister Breda 20022420 • BTW-nr: NL 009960120B01
Handelsnaam van Saint-Gobain Construction Products Nederland B.V.

Verkoopkantoor Nederland • Stuartweg 1b, 4131 NH Vianen

| Essential characteristics Requirement clauses in the european standard | FLEX V218 | FLEX NO18 |
|--|---------------|---------------|
| Thermal resistance and thermal conductivity (4.2.1) | | 0,036 mW/m.K |
| Thickness (4.2.3) | T2 | T2 |
| Reaction to Fire (4.2.6) | A1 | F |
| Water absorption (4.3.7.1) | NPD | NPD |
| Water absorption (4.3.7.2) | NPD | NPD |
| Water vapour transmission (4.3.8) | NPD | NPD |
| Release of dangerous substances (4.3.13) | NPD | NPD |
| Sound absorption (4.3.11) | NPD | NPD |
| Dynamic stiffness (4.3.9) | NPD | NPD |
| Thickness (4.3.10.2) | NPD | NPD |
| Compressability (4.3.10.4) | NPD | NPD |
| Air Flow resistivity (4.3.12) | NPD | NPD |
| Air Flow resistivity (4.3.12) | NPD | NPD |
| Continuous glowing combustion (4.3.15) | NPD | NPD |
| Compressive stress or compressive strength (4.3.3) | NPD | NPD |
| Point load (4.3.5) | NPD | NPD |
| Durability characteristics (4.2.7) ^{a,b} | NPD | NPD |
| Thermal resistance and thermal conductivity (4.2.1) ^c | NPD | NPD |
| Durability characteristics (4.2.7) ^d | NPD | NPD |
| Tensile strength perpendicular to faces ^e (4.3.4) | NPD | NPD |
| Compressive creep (4.3.6) | NPD | NPD |
| CE Designation code | MW-EN13162-T2 | MW-EN13162-T2 |
| CE certificate number | 41531 | SYSTEM 3 |

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation



Saint-Gobain Isover

Hoofdkantoor • Parallelweg 20, 4878 AH Etten-Leur • Tel: 076 508 00 00 • Handelsregister Breda 20022420 • BTW-nr: NL 009960120B01
Handelsnaam van Saint-Gobain Construction Products Nederland B.V.

Verkoopkantoor Nederland • Stuartweg 1b, 4131 NH Vianen

| Essential characteristics Requirement clauses in the european standard | Sonepanel 36 | Isolatieplaat 36 | Comfi Panel 36 |
|--|---------------|------------------|----------------|
| Thermal resistance and thermal conductivity (4.2.1) | 0,036 mW/m.K | 0,036 mW/m.K | 0,036 mW/m.K |
| Thickness (4.2.3) | T3 | 40-140 | 40-140 |
| Reaction to Fire (4.2.6) | A1 | A1 | A1 |
| Water absorption (4.3.7.1) | NPD | NPD | NPD |
| Water absorption (4.3.7.2) | NPD | NPD | NPD |
| Water vapour transmission (4.3.8) | NPD | NPD | NPD |
| Release of dangerous substances (4.3.13) | NPD | NPD | NPD |
| Sound absorption (4.3.11) | NPD | NPD | NPD |
| Dynamic stiffness (4.3.9) | NPD | NPD | NPD |
| Thickness (4.3.10.2) | NPD | NPD | NPD |
| Compressability (4.3.10.4) | NPD | NPD | NPD |
| Air Flow resistivity (4.3.12) | NPD | NPD | NPD |
| Air Flow resistivity (4.3.12) | NPD | NPD | NPD |
| Continuous glowing combustion (4.3.15) | NPD | NPD | NPD |
| Compressive stress or compressive strength (4.3.3) | NPD | NPD | NPD |
| Point load (4.3.5) | NPD | NPD | NPD |
| Durability characteristics (4.2.7) ^{a,b} | NPD | NPD | NPD |
| Thermal resistance and thermal conductivity (4.2.1) ^c | NPD | NPD | NPD |
| Durability characteristics (4.2.7) ^d | NPD | NPD | NPD |
| Tensile strength perpendicular to faces ^e (4.3.4) | NPD | NPD | NPD |
| Compressive creep (4.3.6) | NPD | NPD | NPD |
| CE Designation code | MW-EN13162-T3 | MW-EN13162-T3 | MW-EN13162-T3 |
| CE certificatenumber | 41531 | 41531 | 41531 |

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation



Saint-Gobain Isover

Hoofdkantoor • Parallelweg 20, 4878 AH Etten-Leur • Tel: 076 508 00 00 • Handelsregister Breda 20022420 • BTW-nr: NL 009960120B01
Handelsnaam van Saint-Gobain Construction Products Nederland B.V.

Verkoopkantoor Nederland • Stuartweg 1b, 4131 NH Vianen

10. Les performances du produit identifié aux points 1 et 2 sont conformes aux performances déclarées indiquées au point 9.

La présente déclaration de performances est établie sous la seule responsabilité du fabricant identifié au point 4.

Signé pour le fabricant et en son nom par:

Mark Rippens
Plant Manager Saint-Gobain Isover



Datum: 21-04-2022

Etten-Leur



Saint-Gobain Isover

Hoofdkantoor • Parallelweg 20, 4878 AH Etten-Leur • Tel: 076 508 00 00 • Handelsregister Breda 20022420 • BTW-nr: NL 009960120B01
Handelsnaam van Saint-Gobain Construction Products Nederland B.V.

Verkoopkantoor Nederland • Stuartweg 1b, 4131 NH Vianen